




LMI[®]INDIA
PRECISION TO PERFECTION
An ISO 9001:2015 TUV Nord Certified Company

Single/Dual/Rotational Head ESE *with* Plasma Treatment



Registered supplier with:



18008890626

info@lmiindia.com

www.lmiindia.com



LMI INDIA (P) LTD.

📍 LMI Tower, B-95, Sector 8, Dwarka, New Delhi - 110077, INDIA

☎ +91 11 4993 2552 / 4993 3645 / 4566 7369

Single/Dual/Rotational Head ESE^{with} Plasma Treatment

Sr.No.	Specification	LMI PST01 Single Static Nozzle	LMI PD 02 AA Dual Static Nozzle	LMI PSTR01 Rotational Nozzle
1	Treatment Width	8-16 mm	8-16 mm of each Nozzle	20-75 mm
2	Supply of Voltage	220-230V	220-230V	220-230V
3	Power input	10A/220V	10A/220V	10A/220V
4	<u>Maximum Power</u>	<u>1600 W</u>	<u>3200 W</u>	<u>3200 W</u>
5	<u>Working Pressure</u>	<u>1 to 1.5 bar</u>	<u>1 to 1.5 bar</u>	<u>1 to 1.5 bar</u>
6	External Air	<u>1 to 1.5 bar</u>	<u>1 to 1.5 bar</u>	<u>1 to 1.5 bar</u>
7	Working Power Adjustment	Can set from ScanPro 4 600W to 1600W as per requirements	Can set from ScanPro 4 600W to 1600W as per requirements of each nozzle	Can set from ScanPro 4 600W to 1600W as per requirements
8	Output Cable (L)	3 meter unbreakable metal insulated	3 meter unbreakable metal insulated of each nozzle	3 meter unbreakable metal insulated
9	Dimensions (Nozzle)	245 x 40 x 60 in mm	245 x 40 x 60 in mm of each nozzle	330x 68x 72 in mm
10	Weight	21 KG	35 KG	25Kg
11	Ambient temperature	50-60 Degree Celsius	50-60 Degree Celsius	50-60 Degree Celsius
12	Output Voltage	6 KV-7.5 KV	6 KV-7.5 KV	6 KV-7.5 KV
13	Output Frequency	30-35 KHz	30-35 KHz	30-35 KHz
14	Plasma Current	2.0-30.0 Amp	2.0-30.0 Amp	2.0-30.0 Amp
15	Dimensions	520 x 270 x 500 in mm	520 x 450 x 500 in mm	520 x 270 x 500 in mm
16	Dyne Value	46-54 Dyne/cm	46-54 Dyne/cm	46-54 Dyne/cm
17	Air Interlocking	Available	Available	Available
18	Synchronization with machine	Available , Potential free NO wire are available for external synchronization	Available , Potential free NO wire are available for external synchronization	Available , Potential free NO wire are available for external synchronization
19	Processor	PLC & HMI	PLC & HMI	PLC & HMI



An ISO 9001:2015 TUV Nord Certified Company

LMI India (P) Ltd.

LMI Tower, B-95, Sector 8, Dwarka, New Delhi - 110 077, INDIA

Tel : +91 4566 7369/4993 3645/4993 2552 Email : info@lmiindia.com

Toll Free No.: 18008890626

WORKS

UNIT I

Khasra No 248, Road No 1, Village Bharthal
Sector 26, Dwarka, New Delhi - 110077

UNIT II

F-132, Sector -9, Phase-III
IMT Bawal, Haryana - 123501

Our Network: >Ahmedabad >Bangalore >Bhubaneswar >Chandigarh >Chennai >Gurgaon >Guwahati
>Hyderabad >Indore >Jammu >Jamshedpur >Jodhpur >Kolkata >Lucknow >Mumbai >Pune